

Pixel 64W 4000K SM

Kod produktu: 62901



Dane techniczne:

- Light source power 1x64W
- Info SM
- Luminarie luminous efficacy 117.5 lm/W
- Luminarie luminous flux 8320 Im
- Color temperature 4000K
- Weight 5.59 kg
- Type of equipment AC
- Type of installation Universal mounting
- Housing material Die cast aluminum
- Diffuser material Transparent glass
- Light source **LED**
- Voltage rating 230 V
- Color Black
- Light color White
- Degree of protection (IP) IP66
- · Class of protection II
- CE Yes
- Light source protection Yes
- For ceiling installation, fire class "F" (L) Yes
- Impact resistance IK10
- ENEC Yes

Outdoor floodlight LED luminaire of modern and elegant shape. Designed for newest LED modules of high efficiency. Ideal for lighting facades, gardens, shopping malls, residential areas. Also perfect for illumination of streets, parks and squares.

Versions:

SM - supplied without lens to increase efficiency

AS - asymmetrical lens with vertex at 50°

ST - road lens with asymmetry vertex at 30°

CYC - symmetric road lens ideal for cycle paths

Materials: housing and frame of die cast aluminum with grooves for easier heat dissipation. Covered with thermoset powder paint. 4 mm thick tempered glass.



Installation: wall mounted, to the ground, mounting bracket made of stainless steel included.

Power: 230 V

L W H 395 283 97

L - Length W - Width

H - Height / Depth

