Pixel 32W 4000K AS

Kod produktu: 62904



Dane techniczne:

- Light source power **1x32W**
- Info **AS**
- Luminarie luminous efficacy **117.5 lm/W**
- Luminarie luminous flux **4160 lm**
- Color temperature **4000K**
- Weight **5.66 kg**
- Type of equipment **AC**
- Type of installation **Universal mounting**
- Housing material **Die cast aluminum**
- Diffuser material **Transparent glass**
- Light source **LED**
- Voltage rating **230 V**
- Color **Black**
- Light color **White**
- Degree of protection (IP) **IP66**
- Class of protection **II**
- CE **Yes**
- Light source protection **Yes**
- For ceiling installation, fire class "F" (L) **Yes**
- Impact resistance **IK10**
- ENEC **Yes**

Outdoor floodlight LED luminaire of modern and elegant shape. Designed for newest LED modules of high efficiency. Ideal for lighting facades, gardens, shopping malls, residential areas. Also perfect for illumination of streets, parks and squares.
Versions:
SM - supplied without lens to increase efficiency
AS - asymmetrical lens with vertex at 50°
ST - road lens with asymmetry vertex at 30°
CYC - symmetric road lens ideal for cycle paths

Materials: housing and frame of die cast aluminum with grooves for easier heat dissipation. Covered with thermoset powder paint. 4 mm thick tempered glass.


biuro@elektriko.pl +48 737 449 514

Installation: wall mounted, to the ground, mounting bracket made of stainless steel included.

Power: 230 V

L	W	H
395	283	97

L - Length
W - Width
H - Height / Depth



biuro@elektriko.pl
+48 737 449 514