

DOWNUNDER PURE recessed luminaire, square, white, 4,8W LED warmwhite, 120x155mm

Kod produktu: 66401



Dane techniczne:

- Lamp **planar LED**
- Number of light sources **1**
- Lamp included **Yes**
- Installation depth **3.5 cm**
- Gross weight **0.187 kg**
- Net weight **0.259 kg**
- IP-rating **IP 20**
- Max. wattage **4.8 Watt**
- Protection class **III**
- Colour **white**
- Material **aluminium / steel**
- Remark 1 **Operate with suitable 480mA drivers only**
- Way of mounting **recessed wall mounting**
- Remark 2 **Energy labels in your language are available in the Service Area sub point Download**
- Suitable for lamps from EEC **A**
- Suitable for lamps up to EEC **A++**
- Light distribution type 1 **direct**
- Light distribution type 3 **axisymmetric**
- Length **12 cm**
- Width **15.5 cm**
- Installation length **10.5 cm**
- Installation width **14 cm**
- Depth **3.2 cm**
- Average lifespan **30000 Hours**
- Colour temperature **3000 Kelvin**
- Colour rendering index **80**
- Luminous flux **380 lm**

Aluminum wall luminaire of our DOWNUNDER LED series. The not visibly mounted LED source emits the light indirectly onto the surface to be illuminated. This guarantees glare-free illumination of sidewalks and much more. The DOWNUNDER PURE recessed luminaire is available in white colour version. To operate the luminaire, a suitable LED

driver is required providing 350mA. A mounting frame for installation in masonry can be ordered from the accessory. This luminaire contains built-in LED lamps. EEK: A - A++. The lamps cannot be changed in the luminaire.