

## **Orbit Road At 1c Led2**

Kod produktu: 68567



## Dane techniczne:

The main task of ORBIT LED is illuminating emergency escape routes

Features

- Work Mode non-maintained
- emergency work time **1h**

plus optics, the luminaire mounted on 3m height illuminates 11 meters of escape route maintaining required 1 ix light in

rsal application. ORBIT LED can be used in public buildings, commer

It is designed to work with systems: ST, AT, and CB.

Available mounting: directly on the ceiling.

Technical data:

CATEGORY	VALUE
Power supply	230V 50-60Hz
Power consumption	-1.5VA
Protection class	
Radioelectric interference	Lavel N
Protection degree	1954
Light source	LED1 module
Light source power	20
Luminous flux ROAD	220 m
Luminous flux ROAD PLUS	220 m
Luminous flux SIDE	220 m
Luminous flux AREA	100 m
Light source lifespan	>50.00h
Emergency work time	11, 28, 30
Accumulator type	No CA NT
Accumulator capacity [Ah]	1,635-2,586
Version and housing	4,89



Recharging time	245
Ambient temperature	0.00 P 0.00 P.
Connector	0,5 - 2.5mm <sup>2</sup>

Casing:

Body material: plastic

Casing colour: white

Other colours upon a request