

## **Orbit Road Plus At 2c Led2**

Kod produktu: 68576



## Dane techniczne:

The main task of ORBIT LED is illuminating emergency escape routes

Features

- Work Mode non-maintained
- emergency work time **2h**

plus optics, the luminaire mounted on 3m height illuminates 11 meters of escape route maintaining required 1 ix light in

rsal application. ORBIT LED can be used in public buildings, comme

It is designed to work with systems: ST, AT, and CB.

Available mounting: directly on the ceiling.

## Technical data:

CATEGORY	VALUE
Power supply	230/ 50-6012
Power consumption	<1.5/A
Protection class	· · · · · · · · · · · · · · · · · · ·
Radioelectric interference	Level N
Protection degree	P54
Light source	LED1 module
Light source power	200
Luminous flux ROAD	220 Im
Luminous flux ROAD PLUS	220 Im
Luminous flux SIDE	220 Im
Luminous flux AREA	190 Im
Light source lifespan	-58.00h
Emergency work time	h; th; th;
Accumulator type	N6 Cd HT
Accumulator capacity [Ah]	1,040-2,540
Version and housing	4.89



Recharging time	245
Ambient temperature	0.00 P 0.00 P.
Connector	0,5 - 2.5mm <sup>2</sup>

Casing:

Body material: plastic

Casing colour: white

Other colours upon a request