

Owa Road At 1c Led3 9003

Kod produktu: 68626



Dane techniczne:

- Work Mode **non-maintained**
- emergency work time **1h**

Features:

Owa LED, equipped with LED light source, is a recessed highly efficient luminaire designed for emergency lighting. Its main task is to illuminate emergency escape routes, emergency escape exits and rooms in public facilities, work places, etc. It is compatible with all emergency lighting systems offered by Hybryd. Different versions available.

Technical data:

CATEGORY	VALUE
Power supply	230V 50Hz
Power consumption	<7VA
Protection class	I
Protection degree	IP 20, IP44 (wersja oprawy IP44 na specjalne zamówienie)
Light source	Modul LED (unchangeable light source)
Minimal luminous flux	250 lm
Light source power	3W
Light source lifespan	>50 000h
Accumulator type (according to version)	Ni-MH HT, Ni-Cd HT
Accumulator voltage	4,8V
Accumulator capacity	1,5Ah, 2,5Ah, 4,0Ah
Recharging type	24h
Emergency work time	1h, 2h, 3h
Ambient temperature	+10°C ÷ +40°C
Connector	4 x 0,5 +2,5 mm ² (maintained) 3 x 0,5 +2,5 mm ² (non-maintained)

Casing:

Body material: extruded aluminium

Casing colour: white, black, silver, different colours available