

Owa Road At 3j Led3 9003

Kod produktu: 68646



Dane techniczne:

- Work Mode maintained
- emergency work time 3h

Features

Owa LED, equipped with LED light source, is a recessed highly efficient luminaire designed for emergency lighting. Its main task is to illuminate emergency escape routes, emergency escape routes, emergency scale in an oroma in public lacilities, work place, etc. it is compatible with all emergency lighting systems offered by Hybryd. Different versions available

Technical data:

CATEGORY	VALUE		
Power supply	220V 50Hz		
Power consumption	cTVA		
Protection class	I .		
Protection degree	IP 20, PP44 (wersja oprawy IP44 na specjalne zamówlenie)		
Light source	Modul LED (unchangeable light source)		
Minimal luminous flux	285 Im		
Light source power	SW SW		
Light source lifespan	-50 000h		
Accumulator type (according to version)	NHAM NT, NICO NT		
Accumulator voltage	4,89		
Accumulator capacity	1,5Ah, 2,5Ah, 4,0Ah		
Recharging type	286		
Emergency work time	1h, 2h, 3h		
Ambient temperature	+10°C + +40°C		
Connector	4 x 0,5 +2.5 mm² (maintained)		
	3 x 0,5 +2,5 mm² (non-maintained)		

Ca	si	ng	ı

Body material: extruded aluminium

Casing colour: white, black, silver, different colours available