

Primos Classic At 2c Led5

Kod produktu: 68657



Dane techniczne:

- Work Mode non-maintained
- emergency work time 2h

Features

PRIMOS LEDS, equipped with LED light source, is a highly efficient luminaire designed for emergency lighting. Its main task is to illuminate emergency escape routes, emergency escape exits and rooms in public facilities, work places, etc. It is compatible with all emergency lighting, asystems offered by Hybr

Technical data:

CATEGORY	VALUE				
Power supply	2001 50Hz				
Power consumption	<13,5VA (maintained)				
	<tva (non-maintained)<="" td=""></tva>				
Protection class					
Protection degree	IP 65				
Light source	Modul LED Junchanguable light source)				
Minimal luminous flux	450lm (transparent temp cover)				
	300m (opal lamp cover)				
Light source power	SW				
Accumulator type (according to version)	NS-BRI HT, NS-C4 HT				
Accumulator voltage	487				
Accumulator capacity	2,1Ah, 2,5Ah, 4,0Ah				
Recharging type	246				
Emergency work time	11, 25, 36				
Ambient temperature	+10°C +40°C				
Connector	4 x 0,5 +2,5 mm ² (maintaines)				
	3 x 0,5 +2,5 mm ² (onon-maintained)				

·	a	31	F	g	В

Casing colour:white - RAL 9003

Different colours available

Lamp cover material: plasti

Body material: plast

amp cover: flat and transparent





Mounting types:

