

Primos Road Plus At 2c Led5 T

Kod produktu: 68675



Dane techniczne:

- Work Mode **non-maintained**
- emergency work time **2h**

Model with additional module for work in low temperatures.

Features:

PRIMOS LED5, equipped with LED light source, is a highly efficient luminaire designed for emergency lighting. Its main task is to illuminate emergency escape routes, emergency escape exits and rooms in public facilities, work places, etc. It is compatible with all emergency lighting systems offered by Hybryd.

Technical data:

CATEGORY	VALUE
Power supply	230V 50Hz
Power consumption	<13,5VA (maintained)
	<7VA (non-maintained)
Protection class	I
Protection degree	IP 65
Light source	Modul LED (unchangeable light source)
Minimal luminous flux	450lm (transparent lamp cover)
	300lm (opal lamp cover)
Light source power	5W
Accumulator type (according to version)	Ni-MH HT, Ni-Cd HT
Accumulator voltage	4,8V
Accumulator capacity	2,1Ah, 2,5Ah, 4,8Ah
Recharging type	24h
Emergency work time	1h, 2h, 3h
Ambient temperature	+10°C ÷ +40°C
Connector	4 x 0,5 ÷ 2,5 mm ² (maintained)
	3 x 0,5 ÷ 2,5 mm ² (non-maintained)

Casing:

Casing colour:white - RAL 9003

Different colours available

Lamp cover material: plastic

Body material: plastic

Lamp cover: flat and transparent



Mounting types:

