

Primos Classic At 1j Led5 T

Kod produktu: 68679



Dane techniczne:

- Work Mode maintained
- emergency work time 1h

Model with additional module for work in low temperatures.

Features:	
PRIMOS LEDS equipped with LED light source is a highly efficient luminaire designed for engeneous lighting. Its main task is to illuminate emergency escape mutes, emergency escape mutes, emergency escape mutes, emergency escape mutes, emergency escape mutes.	blic facilities, work places, etc. It is compatible with all emergency lighting systems offered by Hybry

Technical data:

CATEGORY	VALUE
Power supply	230V SOFE
Power consumption	<13,8VA (maintained)
	«FVA (non-maintained)
Protection class	ı
Protection degree	IP 65
Light source	Modul LED (unchangeable light source)
Minimal luminous flux	450m (transparent lamp cover)
	300tm (oparl lamp cover)
Light source power	ow .
Accumulator type (according to version)	NE-MEH HT, NE CO HT
Accumulator voltage	4,814
Accumulator capacity	2.1AA, 2.5Ah, 4.6Ah
Recharging type	28h
Emergency work time	10, 20, 30
Ambient temperature	+10°C +40°C
Connector	4 x 0,5 -2,5 mm ² (mahtained)
	3 v 6 s 25 mm ² (non-ministrated)

Emergency work time	16, 2h, 3h
Ambient temperature	#10°C + +40°C
Connector	4 x 0,5 +2,5 mm ² (maintained)
	3 x 0,5 = 2,5 mm ² (own-maintained)
Casing:	
Casing:	
Casing colour:white - RAL 9003	
Cabing Colour. Write - PAL 5005	
Different colours available	
Lamp cover material: plastic	
Body material: plastic	





Mounting types:

