

# Spark D At J Led W16

Kod produktu: 68753



## Dane techniczne:

- Work Mode **maintained**
- emergency work time **3h**

## Features:

Spark luminaire, equipped with LED light source, is supposed to indicate emergency escape routes and emergency exits with suitable pictograms. Spark can be adopted in public facilities or in workplaces and it is compatible with all emergency lighting systems offered by Hybryd.

## Technical data:

CATEGORY	VALUE
Power supply	230V 50Hz
Power consumption	<4VA
Protection class	I
Protection degree	IP 40
Light source	White LED
Accumulator type	Ni-MH HT, Ni-Cd HT
Recharging type	24h
Emergency work time	3h
Ambient temperature	+10°C ÷ +40°C
Connector	4 x 0,5 ÷ 2,5 mm <sup>2</sup> (maintained) 3 x 0,5 ÷ 2,5 mm <sup>2</sup> (non-maintained) 4 x 0,5 ÷ 1,5 mm <sup>2</sup> (maintained, Mounting W1) 3 x 0,5 ÷ 1,5 mm <sup>2</sup> (non-maintained, Mounting W1)

## Casing:

- body material: aluminium
- casing colour: black (different colours available)
- lamp cover: plexiglass with pictogram
- lamp cover colour: frosted

**PICTOGRAMS:**



**Mounting types:**

