

# Spark Dw St C Led W1

Kod produktu: 68796



## Dane techniczne:

- Work Mode **non-maintained**
- emergency work time **3h**

## Features:

Spark luminaire, equipped with LED light source, is supposed to indicate emergency escape routes and emergency exits with suitable pictograms. Spark can be adopted in public facilities or in workplaces and it is compatible with all emergency lighting systems offered by Hybryd.

## Technical data:

| CATEGORY            | VALUE                                                                                                                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply        | 230V 50Hz                                                                                                                                                                                                              |
| Power consumption   | <4VA                                                                                                                                                                                                                   |
| Protection class    | I                                                                                                                                                                                                                      |
| Protection degree   | IP 40                                                                                                                                                                                                                  |
| Light source        | White LED                                                                                                                                                                                                              |
| Accumulator type    | Ni-MH HT, Ni-Cd HT                                                                                                                                                                                                     |
| Recharging type     | 24h                                                                                                                                                                                                                    |
| Emergency work time | 3h                                                                                                                                                                                                                     |
| Ambient temperature | +10°C ÷ +40°C                                                                                                                                                                                                          |
| Connector           | 4 x 0,5 ÷ 2,5 mm <sup>2</sup> (maintained)<br>3 x 0,5 ÷ 2,5 mm <sup>2</sup> (non-maintained)<br>4 x 0,5 ÷ 1,5 mm <sup>2</sup> (maintained, Mounting W1)<br>3 x 0,5 ÷ 1,5 mm <sup>2</sup> (non-maintained, Mounting W1) |

## Casing:

- body material: aluminium
- casing colour: black (different colours available)
- lamp cover: plexiglass with pictogram
- lamp cover colour: frosted

**PICTOGRAMS:**



**Mounting types:**

