

LC 35W 250mA fixC Ip ADV

Kod produktu: 71558



Dane techniczne:

- Packaging, carton **50 pc(s)**.
- Weight per pc. **0.183 kg**
- Min. forward voltage **47 V**
- Output current **250 mA**
- Max. forward voltage **140 V**
- Max. output power **35 W**
- Packaging, low volume **900 pc(s)**.
- Packaging, high volume **2,700 pc(s)**.
- Input current (at 230 V, 50 Hz, full load) **190 mA**
- Input power (at 230 V, 50 Hz, full load) **39.5 W**
- Max. non-repetitive output peak current **337.5 mA**
- Efficiency (at 230 V, 50 Hz, full load) **90 %**
- tc point **70 °C**
- 110 **110**
- CCC **CCC**
- CE **CE**
- ENEC **ENEC**
- IP20 **IP20**
- RCM **RCM**
- RoHs **RoHs**
- AC voltage range **198 – 264 V**
- Rated supply voltage **220 – 240 V**
- Mains frequency **50 / 60 Hz**
- Overvoltage protection **300 V AC, 1 h**
- λ (at 230 V, 50 Hz, full load) **0.95**
- Dimensions L x W x H **280 x 30 x 21 mm**
- Ambient temperature ta **-20 ... +50 °C**
- Max. output voltage **250 V**
- Output current tolerance **± 5 %**
- THD (at 230 V, 50 Hz, full load)
- Typ. current ripple (at 230 V, 50 Hz, full load)
- Typ. rated current (at 230 V, 50 Hz, full load) **0.19 A**
- Leakage current (PE)
- Time to light

- Fixed output constant current built-in LED Driver
- Output current 250, 300 or 350 mA
- Max. output power 35 W
- Nominal life-time up to 50,000 h
- For class I luminaires
- 5-year guarantee

Properties

- Low profile metal casing with white cover
- Type of protection IP20

Functions

- Intelligent Temperature Guard (overtemperature protection)
- Short-circuit protection
- Overload protection

