PC 1/2x18 TC PRO

Kod produktu: 72335




Dane techniczne:

- Weight per pc. **0.130 kg**
- tc point max. **75 °C**
- Packaging, carton **15 pc(s).**
- DimensionsL x W x H **103 x 67 x 31 mm**
- Packaging, low volume **750 pc(s).**
- Lamp type **TC-TEL**
- Lamp wattage **2 x 18 W**
- Circuit power **37.3 W**
- EEI **A2 BAT**
- Lamp power **34.8 W**
- Current at 50 Hz **0.174 A**
- λ at 50 Hz **0.98**
- Ambient temperature ta **-25 ... +65 °C**
- tc/ta for ≥ 50.000 h **70/60 °C**
- CCC **CCC**
- CE **CE**
- EAC **EAC**
- EL **EL**
- ENEC **ENEC**
- GOST **GOST**
- RCM **RCM**
- RoHs **RoHs**
- AC voltage range **198 – 264 V**
- DC voltage range **176 – 280 V (lamp start ≥ 198 V DC)**
- Mains frequency **0** / **50** / **60 Hz**
- Overvoltage protection **320 V AC, 1 h**
- Type of protection **IP20**
- Mains voltage range **220 – 240 V**
- Defined warm start **≤ 1.6 s**
- Operating frequency **≥ 40 kHz**

- CELMA Energy Efficiency Index A2 BAT / A2
- Nominal life-time up to 50,000 h (at ta 50 °C with a failure rate ≤ 0.2 % per 1,000 h)
- Large temperature range (for values see table)
- Devices can operate either 1 or 2 lamps
- Intelligent Voltage Guard (overvoltage indication and undervoltage shutdown)
- Constant luminous flux irrespective of fluctuations in mains voltage
- For luminaires of protection class I and protection class II

biuro@elektriko.pl +48 737 449 514

- Automatic start after replacement of defective lamps
- Safety shutdown of defective lamps and at end of lamp life (EOL 2)
- For emergency lighting systems as per EN 50172
- For luminaires with M and MM as per EN 60598, VDE 0710 and VDE 0711
- Temperature protection as per EN 61347-2-3 C5e



biuro@elektriko.pl
+48 737 449 514