

# PC 1/2x26-42 TC PRO sr+

Kod produktu: 72340



## Dane techniczne:

- Weight per pc. **0.181 kg**
- tc point max. **75 °C**
- Packaging, carton **25 pc(s)**.
- Dimensions L x W x H **159.4 x 82 x 34 mm**
- Packaging, low volume **550 pc(s)**.
- Lamp type **TC-TEL**
- Lamp wattage **2 x 26 W**
- Circuit power **53.3 W**
- EEI **A2 BAT**
- Lamp power **50.2 W**
- Current at 50 Hz **0.243 A**
- $\lambda$  at 50 Hz **0.99**
- Ambient temperature ta **-25 ... +55 °C**
- tc/ta for  $\geq 50.000$  h **70/50 °C**
- CCC **CCC**
- CE **CE**
- EL **EL**
- ENEC **ENEC**
- GOST **GOST**
- RCM **RCM**
- RoHs **RoHs**
- AC voltage range **198 – 264 V**
- DC voltage range **176 – 280 V (lamp start  $\geq 198$  V DC)**
- Mains frequency **0 / 50 / 60 Hz**
- Type of protection **IP20**
- Mains voltage range **220 – 240 V**
- Defined warm start  $\leq 1.6$  s
- Operating frequency  $\geq 40$  kHz
- CELMA Energy Efficiency Index A2 BAT / A2
- Nominal life-time up to 50,000 h (at ta 50 °C with a failure rate  $\leq 0.2$  % per 1,000 h)
- Large temperature range (for values see table)
- No tools required for installation
- Integrated terminal cover and strain relief
- Through wiring possible
- 3 separate strain reliefs
- Devices can operate either 1 or 2 lamps
- Intelligent Voltage Guard (overvoltage indication and undervoltage shutdown)

- Constant luminous flux irrespective of fluctuations in mains voltage
- For luminaires of protection class I and protection class II
- Automatic start after replacement of defective lamps
- Safety shutdown of defective lamps and at end of lamp life (EOL 2)
- For emergency lighting systems as per EN 50172
- For luminaires with M and MM as per EN 60598, VDE 0710 and VDE 0711
- Temperature protection as per EN 61347-2-3 C5e

