

PC 2x18 T8 TOP sl

Kod produktu: 72362



Dane techniczne:

- Weight per pc. **0.174 kg**
- tc point max. **65 °C**
- Hole spacing D **270 mm**
- Packaging, carton **50 pc(s)**.
- Dimensions L x W x H **280 x 30 x 28 mm**
- Packaging, low volume **900 pc(s)**.
- Lamp type **T8**
- Lamp wattage **2 x 18 W**
- Circuit power **38.6 W**
- EEI **A2**
- Lamp power **32.0 W**
- Current at 50 Hz **0.174 A**
- λ at 50 Hz **0.99**
- Ambient temperature ta **-25 ... +55 °C**
- tc/ta for ≥ 50.000 h **60/50 °C**
- Figure **2**
- Packaging, high volume **2,700 pc(s)**.
- CCC **CCC**
- CE **CE**
- EL **EL**
- ENEC **ENEC**
- GOST **GOST**
- RCM **RCM**
- RoHs **RoHs**
- AC voltage range **198 – 264 V**
- DC voltage range **176 – 280 V (lamp start ≥ 198 V DC)**
- Mains frequency **0 / 50 / 60 Hz**
- Overvoltage protection **320 V AC, 1 h**
- Type of protection **IP20**
- Mains voltage range **220 – 240 V**
- Defined warm start **≤ 1.5 s**
- Operating frequency **≥ 39.5 kHz**
- CELMA Energy Efficiency Index **A2**
- Nominal life-time up to 50,000 h (at ta 50 °C with a failure rate ≤ 0.2 % per 1,000 h)
- Large temperature range (for values see table)

