PC 2x36 T8 TOP sl

Kod produktu: 72363



Dane techniczne:


- Weight per pc. **0.215 kg**
- tc point max. **70 °C**
- Hole spacing D **270 mm**
- Packaging, carton **50 pc(s).**
- DimensionsL x W x H **280 x 30 x 28 mm**
- Packaging, low volume **900 pc(s).**
- Lamp type **T8**
- Lamp wattage **2 x 36 W**
- Circuit power **73.4 W**
- EEI **A2**
- Lamp power **64.0 W**
- Current at 50 Hz **0.330 A**
- λ at 50 Hz **0.99**
- Ambient temperature ta **-25 ... +55 °C**
- tc/ta for ≥ 50.000 h **65/50 °C**
- Figure **2**
- Packaging, high volume **2,700 pc(s).**
- CCC **CCC**
- CE **CE**
- EL **EL**
- ENEC **ENEC**
- GOST **GOST**
- RCM **RCM**
- RoHs **RoHs**
- AC voltage range **198 – 264 V**
- DC voltage range **176 – 280 V (lamp start ≥ 198 V DC)**
- Mains frequency **0** / **50** / **60 Hz**
- Overvoltage protection **320 V AC, 1 h**
- Type of protection **IP20**
- Mains voltage range **220 – 240 V**
- Defined warm start **≤ 1.5 s**
- Operating frequency **≥ 39.5 kHz**


- CELMA Energy Efficiency Index A2
- Nominal life-time up to 50,000 h (at ta 50 °C with a failure rate ≤ 0.2 % per 1,000 h)
- Large temperature range (for values see table)

biuro@elektriko.pl +48 737 449 514

- Constant luminous flux irrespective of fluctuations in mains voltage
- Lamp preheating for min. 30,000 starts without replacement of lamps
- Designed for THD < 10 %
- For luminaires of protection class I and protection class II
- Automatic start after replacement of defective lamps
- Safety shutdown of defective lamps and at end of lamp life
- Push terminal for rapid automatic or manual wiring
- For emergency lighting systems as per EN 50172







biuro@elektriko.pl +48 737 449 514