

PC 2x18 T8 TEC

Kod produktu: 72384



Dane techniczne:

- Weight per pc. **0.107 kg**
- tc point max. **65 °C**
- Hole spacing D **138 mm**
- Packaging, carton **60 pc(s)**.
- Dimensions L x W x H **150 x 40 x 28 mm**
- Packaging, low volume **1,260 pc(s)**.
- Lamp type **TC-L**
- Lamp wattage **2 x 18 W**
- Circuit power **34.0 W**
- EEI **A2**
- Lamp power **30.5 W**
- Current at 50 Hz **0.16 A**
- λ at 50 Hz **0.95**
- Ambient temperature ta **-10 ... +50 °C**
- Packaging, high volume **3,780 pc(s)**.
- ÖVE **ÖVE**
- CCC **CCC**
- CE **CE**
- EAC **EAC**
- RCM **RCM**
- RoHs **RoHs**
- AC voltage range **198 – 264 V**
- Mains frequency **50 / 60 Hz**
- Overvoltage protection **320 V AC, 1 h (280 V AC, 48 h for 2x58 W applications)**
- Time to light $\leq$ **2 s**
- Type of protection **IP20**
- Mains voltage range **220 – 240 V**
- Operating frequency **> 40 kHz**
- CELMA Energy Efficiency Index **A2**
- Nominal life-time up to 30,000 h (at ta 50 °C with a failure rate $\leq$ 0.3 % per 1,000 h)
- Large temperature range (for values see table)
- Lamp preheating for min. 30,000 starts without replacement of lamps
- Automatic start after replacement of defective lamps
- Push terminal for rapid automatic or manual wiring
- Temperature protection as per EN 61347-2-3 C5e

