

PCA 1x35/49/80 T5 EXCEL one4all Ip xitec II

Kod produktu: 72420



Dane techniczne:

- Weight per pc. **0.244 kg**
- Ambient temperature t_a **-25 ... +60 °C**
- t_c point max. **80 °C**
- Hole spacing D **350 mm**
- Packaging, carton **10 pc(s)**.
- Packaging, pallet **760 pc(s)**.
- Dimensions L x W x H **360 x 30 x 21 mm**
- Lamp type **TC-L**
- Lamp wattage **1 x 80 W**
- Circuit power **85.5 W**
- EEI **A1 BAT**
- Lamp power **80 W**
- Current at 230 V, 50 Hz **0.36 A**
- λ at 230 V, 50 Hz **0.98**
- CE **CE**
- EAC **EAC**
- EL **EL**
- EMCVDE **EMCVDE**
- ENEC **ENEC**
- RCM **RCM**
- RoHs **RoHs**
- AC voltage range **198 – 264 V**
- DC voltage range **176 – 280 V (lamp start $\geq$ 198 V DC)**
- Mains frequency **0 / 50 / 60 Hz**
- Overvoltage protection **320 V AC, 1 h**
- Dimming range **1 – 100 %**
- Type of protection **IP20**
- Typ. power input on stand-by
- Mains voltage range **220 – 240 V**
- Operating frequency **~ 40 – 130 kHz**
- Lamp start possible from **1 %**
- Protective hot restart **0.5 s for AC / 0.2 s for DC**
- Processor-controlled ballast with xitec II inside
- Highest possible energy class CELMA EEI = A1 BAT (1)

