TE VIPER 60 VA

Kod produktu: 72531




Dane techniczne:

- Weight per pc. **0.102 kg**
- Ambient temperature ta **0 ... +50 °C**
- tc point max. **70 °C**
- Rated current (at 230 V, 50 Hz) **0.26 A**
- Packaging, carton **20 pc(s).**
- DimensionsL x W x H **120 x 40 x 29 mm**
- Operating frequency **55 kHz**
- Packaging, low volume **280 pc(s).**
- Lamp power **20 – 60 VA**
- Packaging, high volume **3,920 pc(s).**
- Secondary voltage 230 V **11.3 V**
- Secondary voltage 240 V **11.6 V**
- Secondary terminal **2-pin**
- Max. torque terminal block **0.4 Nm**
- Output terminal **2-pin**
- Stripping length (primary / secondary) **8 mm**
- Terminal diameter on each pole **Max. 2.5 mm² Min. 1.5 mm²**
- 110 **110**
- CE **CE**
- EAC **EAC**
- ENEC **ENEC**
- Independent gear **Independent gear**
- MM **MM**
- RoHs **RoHs**
- SC2 - Protection Class 2 **SC2 - Protection Class 2**
- Short Circuit Proof **Short Circuit Proof**
- dimmerLC **dimmerLC**
- Mains frequency **50** / **60 Hz**
- λ **> 0.95**
- Efficiency **> 93 %**
- Dimming **Leading-edge and trailing-edge phase control**
- Max. cable length secondary **2 m**
- Type of protection **IP20**
- Mains voltage range **230 – 240 V**
- Soft-start

- Protection class **II**

biuro@elektriko.pl +48 737 449 514

- Short-circuit shutdown feature with automatic restart
- Compact dimensions
- Overtemperature and overload protection
- Large connection compartment
- With soft start (< 1 s)
- Double assignment of the terminal possible
- Screw terminals for rigid and flexible wires
- Ground terminal for through-wiring
- Rapid installation of cable clamp and terminal cover, no tool required
- Not suitable for operation with MR16 LED bulbs



biuro@elektriko.pl
+48 737 449 514