

Screw terminal

Kod produktu: 72536



Dane techniczne:

- Weight per pc. **0.050 kg**
- Packaging, carton **400 pc(s)**.
- Packaging, low volume **1,600 pc(s)**.
- Figure **2**
- Packaging, high volume **8,000 pc(s)**.
- 120 **120**
- CE **CE**
- EAC **EAC**
- RoHs **RoHs**
- SELV **SELV**
- Short Circuit Proof **Short Circuit Proof**
- dimmerLC **dimmerLC**
- doppelte Isolierung **doppelte Isolierung**
- Mains frequency **50 / 60 Hz**
- $\lambda > 0.95$
- Efficiency **> 92 %**
- Dimming **Leading-edge and trailing-edge phase control**
- Max. cable length secondary **2 m**
- Type of protection **IP20**
- Mains voltage range **220 – 240 V**
- Soft-start
- Protection class **II**
- Life-time **30,000 h**
- Nominal life-time up to 30,000 h (at max ta 50 °C with a failure rate $\leq 0.2 \%$ per 1,000 h)
- Compact dimensions
- Screw terminals for rigid and flexible wires
- Inbuilt transformer
- Able to drive any low-voltage lamp on the market up to max. 60 W
- Coloured single packaging (optional)
- Short-circuit shutdown feature with automatic restart
- Overload protection

