

HF-E 1/2 58 TL-D II 220-240 50/60Hz

Kod produktu: 72818



Dane techniczne:

- Full product name **HF-E 1/2 58 TL-D II 220-240 50/60Hz**
- Rated Lamptype **TL-D**
- Rated Ballast-Lamp Power **58**
- Rated Number of Lamps **1 piece**

Essentially smart and reliable HF-Essential is the most cost-effective, slim and affordable ballast to reliably operate a fluorescent lamp. It is also the ideal entry-level product for EM system users who want to enjoy the benefits offered by electronic ballasts. The cost-saving and reliable HF-Essential has an energy efficiency class A2, and its robust design meets all relevant international safety and performance standards. HF-Essential is intended for use with indoor lighting fixtures such as recessed luminaires, which are largely used in office, industrial, hotel, restaurant and other applications.

Essentially smart and reliable HF-Essential is the most cost-effective, slim and affordable ballast to reliably operate a fluorescent lamp. It is also the ideal entry-level product for EM system users who want to enjoy the benefits offered by electronic ballasts. The cost-saving and reliable HF-Essential has an energy efficiency class A2, and its robust design meets all relevant international safety and performance standards. HF-Essential is intended for use with indoor lighting fixtures such as recessed luminaires, which are largely used in office, industrial, hotel, restaurant and other applications.

Features

Complies with CE and Kema

Robust design for 45,000 hours lifetime at $T_a=50\text{ }^{\circ}\text{C}$ and over 6,000 on/off switching operations on one lamp

Energy efficiency class: A2

Failure rate of 0.3% per 1,000 hours at $T_c \text{ max} = 75\text{ }^{\circ}\text{C}$

Igniter and capacitor not required; flicker-free and noiseless

Applications

Ideal for applications where there is a need to reduce the wattage per square meter or to reduce operating costs

Indoor applications such as office buildings, hospitals, supermarkets, department stores, homes and schools