

# Swing Led 15w 4000k Biały Wąskokątny

Kod produktu: 73686



## Dane techniczne:

- Rated power **15W**
- Colour temperature **4000K**
- Energy efficiency class **EEL=A**
- Luminous flux **1100lm**
- Type of the diffuser **MAT**
- Mounting version **Recessed**
- Power supply 230V **Power supply 230V**
- Declaration of conformity CE **Declaration of conformity CE**
- Ingress protection IP40 **Ingress protection IP40**
- LED **LED**

## Specification:

Recessed frameless downlight fitting equipped with modern and energy-saving light source COB LED. The body made of plastic, steel and aluminium ensures a long-term operation of the fitting. The diffuser made of highly transparent PMMA guarantees high luminous flux and ensures optimal conditions for the LED operation. Due to the possibility of adjusting the light direction vertically up to 30° and horizontally (turn) up to 355°, four options of diffuser to choose: 65°, 25°, 59°/92°, as well as modern and elegant design, the fitting is suitable for a variety of applications.

## Application:

Recessed fitting suitable for mounting in plasterboard ceilings, dedicated for indoor use as a basic or accent lighting. Due to modern and elegant design and the possibility of choosing the optimal light distribution, the fitting is ideal for offices, commercial buildings and passageways.



