

Codar Rs Led Evo Rcr 40w Pc Ip66 4000k 1569mm

Kod produktu: 73811



Dane techniczne:

- Rated power 40W
- Colour temperature 4000K
- Energy efficiency class EEI=A+
- Luminous flux 5200lm
- Type of the diffuser MAT
- Mounting version Surface/Suspended
- Power supply 230V Power supply 230V
- Declaration of conformity CE Declaration of conformity CE
- LED LED
- Electrical protection class 1 Electrical protection class 1
- Ingress protection IP66 Ingress protection IP66
- Impact resistance IK09 Impact resistance IK09

Specification:

Dustproof and moistureproof, surface mounted or suspended, vandal resistant, high efficiency LED luminaire with extended tightness IP66. Equipped with energy saving light sources LED GO! Body made of polycarbonate with silicon gasket and special multilayer diffuser combining high impact resistant, UV stabilized prismatic polycarbonate cover. CRI>80, led lifespan of 50.000h (L70B50) ta=25°C.

Application:

Multi-purpose LED fixture designed for use in areas with high levels of dust and moisture. Especially recommended for parking (including underground and multi-level), sports stadiums, warehouses, transport terminals, subways, factories. Suitable for new applications as well as for replacing conventional T8 & T5 fittings with energysaving LED solutions. Construction of the fitting dedicated for non-invasive surface or suspended mounting using included accessory installation kit.

Visit our new CODAR RS LED EVO site!





