Pillar Mini Led N 3w 3000k 15st. Czarny

Kod produktu: 74247



Dane techniczne:

- Rated power **3W**
- Colour temperature **3000K**
- Energy efficiency class **EEI=A**
- Luminous flux **200lm**
- Mounting version **Surface**
- Power supply 230V **Power supply 230V**
- Declaration of conformity CE **Declaration of conformity CE**
- LED **LED**
- Electrical protection class 1 **Electrical protection class 1**
- Ingress protection IP54 **Ingress protection IP54**

Specification:
Outdoor facade LED luminaire with a power of 1x3W and 2x3W provides economical and long-term operation without replacing light sources. Luminaire with the IP54 parameter is dustproof and provides protection against drops of water falling at any angle from all sides. Ingress protection class is provided by its design - aluminum body and tempered glass, additionally secured with a seal. Available in two light distribution options: 15° and 30°. Specification: temperature 3000K, 4000K, 5000K; light color white, and optionally: red, blue and green.

Application:
The fitting for wall mounting (directly on the surface using dowels) is designed specifically for outdoor accent lighting of building facades such as: hotels, offices, apartment buildings, but also private homes, passageways and exit areas.



biuro@elektriko.pl +48 737 449 514



biuro@elektriko.pl +48 737 449 514