

HF-S 158 TL-D II 220-240V 50/60Hz

Kod produktu: 74719



Dane techniczne:

- Line Frequency **50/60 Hz**
- Lifetime 90% surv.@Tcaselife **50000 hr**
- Line Voltage **220-240 V**
- C-Tick certificate **Yes**
- TISI marking **Yes**
- CB Certificate **Yes**

Product family information

HF-Selectalume II TL-D is the most cost-effective, reliable and outstanding solution for fluorescent lamps. These ballasts are part of an overall high-efficiency lighting system that may help you or your customers to achieve any international or local energy code you need to comply with. HF-Selectalume II TL-D ballasts are the ideal choice for a broad range of new construction and retrofit applications within the commercial sector, including general surface mounting or office lighting, parking garages, warehouses, waterproof and other applications.

Features

Highest CELMA Energy Efficiency Index A2 BAT*

Complies with CE, ENEC, EL, VDE-EMC, CCC marks of conformity

Average nominal service lifetime over 85,000 hours (at Ta 50°C) with a failure rate ≤ 0.1 % per 1,000 hours)

Optimized lamp preheating for min 50,000 On/Off switch operations without replacement of lamps

Applications

Suitable for DC operation and emergency lighting installations; full compliance with requirements for emergency lighting according to EN 61347-2-3 -annex J

For applications with high switching activity, e.g. where movement-detection control devices are used

For luminaires of protection class I and protection class II used in office buildings, hospitals, supermarkets, department stores, industrial premises and schools

