



## Balti 220



External LED luminaire with direct-indirect and direct light distribution. Great for illumination of promenades, halls, corridors, passages or alleys.

**Materials:** powder painted die-cast aluminum with special antioxidant coating which ensures height resistance from external factors. Diffuser made of transparent thermoplastics. INOX screws

**Installation:** wall mounted

**Power:** 230 V

### ELECTRICAL DATA

Light source	LED
Type of equipment	AC
Voltage rating	230 V
Light source included	Yes

### MECHANICAL DATA

Type of installation	Wall mounted
Housing material	Die cast aluminum
Electrical track connection	No

### INFORMATIONS

Control	Bez
Rotated model	No

### MATERIALS


Product code	Light source power [W]	Luminaire luminous flux [lm]	Light distribution	Color	Info
IV119803	2×26	2700	DI/IN	Grey	-
IV119804	2×26	2700	DI/IN	White	-
IV119903	1×33	3400	DI/IN	Grey	IN 1,5W 5°
IV119904	1×33	3400	DI/IN	White	IN 1,5W 5°
IV119703	1×18	2000	DI/IN	Grey	IN 12W 44°
IV119704	1×18	2000	DI/IN	White	IN 12W 44°
IV119603	1×37	4200	DI	Grey	-
IV119604	1×37	4200	DI	White	-

### CERTIFICATES

Degree of protection (IP)	IP66
Class of protection	I
Light source protection	Yes
CE	Yes
ENEC	Yes
For ceiling installation, fire class "F" (L)	Yes

### LIGHT DATA

Color rendering index	80
Color temperature	3000K
Light distribution	Wide beam
Beam angle	100°



## DIMENSIONS

L [mm]	W [mm]	H [mm]
225	166	56

L = Length | W = Width | H = Height / Depth