FPXF LIGHTING



Duet LED











Wall mounted luminaire with high power and efficient LED COB (Chip-On-Board) light sources from renowned producers. LED COB lighting is characteristic for its low failure rate, no multipoint emission effect, resistance to voltage fluctuations and comfortable light without pulsation effect. LED diffuser has been applied for better light distribution.

Materials: powder painted aluminum housing (standard

color: grey), transparent PC plate

Installation: wall mounted

Power: 230 V

ELECTRICAL DATA

Light source	LED
Number of light sources	2
Light source power	4W
Type of equipment	AC
Voltage rating	230 V
Light source included	Yes
Luminarie power	8 W
SELV	Yes

MECHANICAL DATA

Type of installation	Wall mounted
Housing material	Aluminum

INFROMATIONS

Color	Grey
-------	------

CERTIFICATES

Degree of protection (IP)	IP54
Class of protection	I
Light source protection	Yes
Energy class	A
CE	Yes

LIGHT DATA

Light color	White
Light distribution	Very narrow beam
Light distribution	DI/IN
Class of luminarie	I


OPTICAL DATA

Louver/shutter	Transparent plastic
Diffuser color	None
Diffuser material	Transparent plastic
Reflector	None

MATERIALS

Product code	Light source power [W]	Luminarie luminous flux [lm]	Luminarie luminous efficacy [lm/W]	Color temperature [K]	Beam angle [°]
PX1001331	2×4	268	79	2900	20
PX1001336	2×4	275	80	5400	20
PX1001343	2×4	268	79	2900	40
PX1001349	2×4	275	80	5400	40

FPXF LIGHTING



DIMENSIONS

L [mm]	W [mm]	H [mm]
70	50	154

 $L = Length \mid W = Width \mid H = Height / Depth$

MOUNTING HOLES



B = Spacing width