

VIP G/K IP44



VIP series luminaire of direct light distribution and increased tightness. Made of thickwalled aluminum profile of high endurance, suitable for T5 fluorescent lamps. VIP IP44 version cannot be combined in a lines. Luminaire was designed for installations under the ledges and roofs, in the underpasses, bathrooms and any other places requiring increased degree of tightness. End caps in set.

Materials: powder painted aluminum profile (standard color: grey), polycarbonate opal diffuser, end caps included

Installation: for cardboard ceiling

Accessories: suspension (simple, electric)

Power: 230 V

ELECTRICAL DATA

Light source	T5
Lamp holder	G5
Number of light sources	1
Type of equipment	EVG
Voltage rating	230 V

MECHANICAL DATA

Type of installation	For 600x600 ceiling
Housing material	Aluminum

INFROMATIONS

Color	Grey
-------	------

CERTIFICATES

Degree of protection (IP)	IP44
Class of protection	I
Light source protection	Yes
Energy class	A
CE	Yes
PZH	Yes

LIGHT DATA

Light distribution	DI
--------------------	----



OPTICAL DATA

Louver/shutter	OPAL
Diffuser color	White
Diffuser material	Opal/mat plastic
Reflector	High gloss

MATERIALS

Product code	Light source power [W]	Weight [kg]
PX0976501	1×14	2.0
PX0976508	1×24	2.0
PX0976515	1×21	2.6
PX0976522	1×39	2.6
PX0976529	1×28	3.2
PX0976536	1×54	3.2
PX0976543	1×35	3.8
PX0976550	1×49	3.8
PX0976557	1×80	3.8

DIMENSIONS



Product code	L [mm]	W [mm]	H [mm]
PX0976501	583	65	65
PX0976508	583	65	65
PX0976515	883	65	65
PX0976522	883	65	65
PX0976529	1183	65	65
PX0976536	1183	65	65
PX0976543	1483	65	65
PX0976550	1483	65	65
PX0976557	1483	65	65

L = Length | W = Width | H = Height / Depth