FPXF LIGHTING



ELECTRICAL DATA

Light source	LED
Number of light sources	1
Type of equipment	AC
Voltage rating	230 V
Light source included	Yes

MECHANICAL DATA

Housing material	Steel sheet
Electrical track connection	No

INFROMATIONS

Color	Grey
Rotated model	No

Cube DLN LED











000

Cubic lighting luminaire of modern design combined with LED technology makes Cube DLN a great solution for lighting both office spaces and aisles. Simple construction and austere design relate to modern interior design aesthetics. LED light source has an integrated heat sink that allows free flow of air around the LED source and therefore more efficient cooling.

Materials: powder painted housing made of steel sheets

(standard color: grey)

Installation: ceiling mounted, suspended

Accessories: suspensions

Power: 230 V

CERTIFICATES

Degree of protection (IP)	IP20
Class of protection	1
Energy class	A
CE	Yes
For ceiling installation, fire class "F" (L)	Yes

LIGHT DATA

Light distribution	DI
LIGITE GISTIDUTION	


OPTICAL DATA

Reflector None	
----------------	--

MATERIALS

Product code	Light source power [W]	Type of installation	Luminarie Iuminous flux [lm]	Luminarie Iuminous efficacy [lm/W]	Color temperature [K]	Beam angle [°]
PX4021001	1×12	Ceiling mounted	885	75	3000	45
PX4021008	1×12	Ceiling mounted	965	82	4000	45
PX4021015	1×18	Ceiling mounted	1230	68	3000	40
PX4021022	1×18	Ceiling mounted	1300	72	4000	40
PX4021029	1×23	Ceiling mounted	1880	82	3000	40
PX4021036	1×23	Ceiling mounted	1990	87	4000	40
PX4021057	1×12	Suspended	885	75	3000	45
PX4021064	1×12	Suspended	965	82	4000	45
PX4021071	1×18	Suspended	1230	68	3000	40
PX4021078	1×18	Suspended	1300	72	4000	40
PX4021085	1×23	Suspended	1880	82	3000	40
PX4021092	1×23	Suspended	1990	87	4000	40

FPXF LIGHTING



DIMENSIONS

L [mm]	W [mm]	H [mm]
160	160	160

 $L = Length \mid W = Width \mid H = Height / Depth$