

Miniten



Wall mounted luminaire of direct-indirect light distribution. High IP 66 protection class allow both indoor and outdoor use. Dedicated for illumination of architectural elements, building facades, paths and sidewalks.

Materials: housing made of die cast aluminum with high resistance to chemicals, corrosion and acid vapors, stainless steel connectors, tempered glass resistant to temperature and mechanical damage, silicone seals

Installation: wall mounted

Accessories: optic lenses of different beam angles, shutter, double lens (for halogen version)

Power: 230 V

ELECTRICAL DATA

Voltage rating	230 V
----------------	-------

MECHANICAL DATA

Type of installation	Wall mounted
Housing material	Die cast aluminum

INFORMATIONS

Color	Grey
-------	------

CERTIFICATES

Degree of protection (IP)	IP66
Impact resistance	IK10
Class of protection	I
Light source protection	Yes
CE	Yes
ENEC	Yes

LIGHT DATA

Light distribution	DI/IN
--------------------	-------


OPTICAL DATA

Louver/shutter	SH
Diffuser color	None
Diffuser material	Transparent glass
Reflector	None

MATERIALS

Product code	Light source	Light source power [W]	Light source luminous flux [lm]	Color temperature [K]	Beam angle [°]
IV10531243	LED	2×6	680	3000	61
IV10231243	LED	2×3	200	3500	61
IV10231203	LED	2×3	200	3500	5
IV103203	HS	1×40	-	-	4

DIMENSIONS



L [mm]	W [mm]	H [mm]
125	90	104

L = Length | W = Width | H = Height / Depth

ACCESSORIES

Optical elements

Miniten Lens for LED version

Miniten Shutter for LED version

Miniten Double lens for halogen version