

EC Declaration of Conformity

NR 199/30/09/14

The company:

PXF LIGHTING
UL. JUTRZENKI 73
02-230 WARSZAWA

Hereby declare on our own responsibility, that the product:

Product name: **ROMA II IP65 LED**

Product numer: Annex

is in conformity with the following directives

2006/95/EC LVD

2004/108/WE EMC

2011/65/EC RoHS

and with the following standards

PN-EN 60598-1:2011	Luminaires - Part 1: General requirements and tests
PN-EN 60598-2-2:2012	Luminaires - Part 2-2: Particular Requirements - Recessed luminaires
PN-EN 60598-2-22:2004/A2:2010	Luminaires - Part 2-22: Particular Requirements - Luminaires for emergency lighting
PN-EN 61547:2009	Equipment for general lighting purposes - Electromagnetic immunity requirements
PN-EN 61000-3-2:2007/A2:2010	Electromagnetic Compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)
PN-EN 61000-3-3:2013-10	Electromagnetic Compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection
PN-EN 62493:2010	Assessment of lighting equipment related to human exposure to electromagnetic fields
PN-EN 62031:2010/A1:2013-06	LED modules for general lighting - Safety specifications
PN-EN 62471:2010	Photobiological safety of lamps and lamp systems

Implementation year of the EC regulation: **14**

Michał Samra

R&D Department

PXF Lighting
mgr inż. Jacek Bieniak
02-230 Warszawa, ul. Jutrzenki 73
tel.: (022) 33 44 000
NIP: 951-002-66-64

ANNEX

KOD	NAZWA
PX3715001	Roma II IP65 LED 44W 3000K OPAL 600x600
PX3715008	Roma II IP65 LED 44W 4000K OPAL 600x600
PX3715015	Roma II IP65 LED 55W 3000K OPAL 300x1200
PX3715022	Roma II IP65 LED 55W 4000K OPAL 300x1200

KOD	NAZWA
PX3715029	Roma II IP65 LED 44W 3000K MPRM 600x600
PX3715036	Roma II IP65 LED 44W 4000K MPRM 600x600
PX3715043	Roma II IP65 LED 55W 3000K MPRM 300x1200
PX3715050	Roma II IP65 LED 55W 4000K MPRM 300x1200