

Balti 80



External LED luminaire with direct-indirect and direct light distribution. Great for illumination of promenades, halls, corridors, passages or alleys.

Materials: powder painted die-cast aluminum with special antioxidant coating which ensures height resistance from external factors. Diffuser made of transparent thermoplastics. INOX screws.

Installation: wall mounted

Power: 230 V

ELECTRICAL DATA

Light source	LED
Number of light sources	1
Light source power	6.5W
Type of equipment	AC
Voltage rating	230 V
Light source included	Yes
Luminaire power	6.5 W

MECHANICAL DATA


Type of installation	Wall mounted
Housing material	Die cast aluminum
Electrical track connection	No

INFORMATIONS

Control	Bez
Rotated model	No

MATERIALS

Product code	Light source power [W]	Color
IV119303	1×6.5	Grey
IV119304	1×6.5	White



DIMENSIONS

L [mm]	W [mm]	H [mm]
83	153	46

L = Length | W = Width | H = Height / Depth

CERTIFICATES

Degree of protection (IP)	IP66
Class of protection	I
Light source protection	Yes
CE	Yes
ENEC	Yes
For ceiling installation, fire class "F" (L)	Yes

LIGHT DATA

Light source luminous flux	550 lm
Luminaire luminous flux	550 lm
Color rendering index	80
Color temperature	3000K
Light distribution	Wide beam
Light distribution	DI
Beam angle	110°