



Balti 150



External LED luminaire with direct-indirect and direct light distribution. Great for illumination of promenades, halls, corridors, passages or alleys.

Materials: powder painted die-cast aluminum with special antioxidant coating which ensures height resistance from external factors. Diffuser made of transparent thermoplastics. INOX screws

Installation: wall mounted

Power: 230 V

ELECTRICAL DATA

Light source	LED
Number of light sources	1
Type of equipment	AC
Voltage rating	230 V
Light source included	Yes

MECHANICAL DATA


Type of installation	Wall mounted
Housing material	Die cast aluminum
Electrical track connection	No

INFRMATIONS

Control	Bez
Rotated model	No

MATERIALS

Product code	Light source power [W]	Luminaire luminous flux [lm]	Color
IV118303	1×26	2700	Grey
IV118304	1×26	2700	White
IV118503	1×12	1500	Grey
IV118504	1×12	1500	White



DIMENSIONS

L [mm]	W [mm]	H [mm]
158	163	48

L = Length | W = Width | H = Height / Depth

CERTIFICATES

Degree of protection (IP)	IP66
Class of protection	I
Light source protection	Yes
CE	Yes
ENEC	Yes
For ceiling installation, fire class "F" (L)	Yes

LIGHT DATA

Color rendering index	80
Color temperature	3000K
Light distribution	Wide beam
Light distribution	DI
Beam angle	110°