



PF30



Extremely thin ceiling luminaire, especially designed for LED light sources. Perfect for discrete and elegant interior lighting.

Materials: polyester painted housing with modern heat dissipation system made of die cast aluminum (standard colors: white, silver, black), faceted, metalized and durable reflector made of polycarbon, polycarbonate opal diffuser

Installation: ceiling mounted

Power: 230 V

ELECTRICAL DATA

Light source	LED
Number of light sources	1
Type of equipment	AC
Voltage rating	230 V
Light source included	Yes

MECHANICAL DATA

Type of installation	Ceiling mounted
Housing material	Die cast aluminum

MATERIALS

Product code	Light source power [W]	Louver/shutter	Beam angle [°]	Color	Degree of protection (IP)
IV3886-02-16	1×26	-	120	Black	IP20
IV3886-02-21	1×26	-	120	White	IP20
IV3886-02-52	1×26	-	120	Grey	IP20
IV3887-01-16	1×18	OPAL	110	Black	IP44
IV3887-01-21	1×18	OPAL	110	White	IP44
IV3887-01-52	1×18	OPAL	110	Grey	IP44
IV3888-02-16	1×26	OPAL	100	Black	IP44
IV3888-02-21	1×26	OPAL	100	White	IP44
IV3888-02-52	1×26	OPAL	100	Grey	IP44


CERTIFICATES

Class of protection	I
CE	Yes
ENEC	Yes

LIGHT DATA

Color temperature	3000K
Light distribution	DI

DIMENSIONS



H [mm]	F [mm]
--------	--------

40	300
----	-----

H = Height / Depth | F = Outer diameter

