



OW LED



OW LED to seria regulowanych oczek ledowych przeznaczonych do oświetlenia akcentującego wnętrz.

Materials: powder painted aluminum housing (standard color: white); chrome version also available; two axis adjustable LED; two light distributions available: with a focused beam 20° and diffused beam 40°

Installation: for cardboard ceiling

Power: 230 V

ELECTRICAL DATA

Light source	LED
Number of light sources	1
Light source power	4W
Type of equipment	AC
Voltage rating	230 V
Light source included	Yes
Luminarie power	4 W

MECHANICAL DATA

Type of installation	For 600x600 ceiling
Housing material	Aluminum

MATERIALS



Product code	Light source power [W]	Color temperature [K]	Beam angle [°]	Color	Weight [kg]
PX0864301	1×4	2900	20	White	0.80
PX0864308	1×4	5400	20	White	0.80
PX0864315	1×4	2900	40	White	0.80
PX0864322	1×4	5400	40	White	0.80
PX0864401	1×4	2900	20	Chrome	0.32
PX0864408	1×4	5400	20	Chrome	0.32
PX0864415	1×4	2900	40	Chrome	0.32
PX0864422	1×4	5400	40	Chrome	0.32

CERTIFICATES

Degree of protection (IP)	IP20
Class of protection	I
Energy class	A
CE	Yes

LIGHT DATA

Light distribution	DI
--------------------	----



DIMENSIONS

Product code	H [mm]	F [mm]
PX0864301	100	118
PX0864308	100	118
PX0864315	100	118
PX0864322	100	118
PX0864401	75	103
PX0864408	75	103
PX0864415	75	103
PX0864422	75	103

H = Height / Depth | F = Outer diameter

MOUNTING HOLES

Product code	A [mm]	B [mm]
PX0864301	109	109
PX0864308	109	109
PX0864315	109	109
PX0864322	109	109
PX0864401	95	95
PX0864408	95	95
PX0864415	95	95
PX0864422	95	95

A = Spacing length | B = Spacing width