



## Soul



Street luminaires for discharge lamps and LED. Application: street and sidewalks lighting, squares, parking lots, parks and other urban spaces.

**Materials:** frame with a grid (surface mounted version), masking frame (recessed version), CLA device, housing made of die cast aluminum protected with thermo hardened polyester cover, reflector made of polished aluminum of 99,85% purity, 4mm thick transparent tempered glass

**Installation:** pole mounted

**Power:** 230 V

### ELECTRICAL DATA

Number of light sources	1
Type of equipment	VVG
Ingiter included	Yes
Voltage rating	230 V

### MECHANICAL DATA

Type of installation	Pole mounted
Housing material	Die cast aluminum

### INFROMATIONS

Color	Black
-------	-------

### CERTIFICATES

Degree of protection (IP)	IP65
Impact resistance	IK10
Class of protection	II
Light source protection	Yes
Energy class	A+
CE	Yes

### LIGHT DATA

Light distribution	DI
--------------------	----

### OPTICAL DATA

Louver/shutter	SH
Diffuser color	None
Diffuser material	Transparent glass
Reflector	High gloss

### MATERIALS

Product code	Light source	Lamp holder	Light source power [W]	Weight [kg]
CL505123.170	HIT/HST	E27	1×70	7.95
CL505123.110	HST	E40	1×100	8.45
CL505123.115	HST	E40	1×150	8.80
CL505223.110	HIT	E27	1×100	8.40
CL505223.115	HIE	E27	1×150	8.70

